



TYPICAL GUTTER SECTION
UNDER SLAB APPLICATION

() - Denotes Millimeters

DIMENSION CHART			
MODEL	Max. Allowed Opening	Max Opening at Installation	
		w/ ±50% Mv't	w/ ±100% Mv't
USG-12N	5" (127)	3-1/4" (83)	2-1/2" (64)
USG-18N	11" (279)	7-1/4" (184)	5-1/2" (140)
USG-24N	17" (432)	11-1/4" (286)	8-1/2" (216)
USG-30N	23" (584)	15-1/4" (387)	11-1/2" (286)
USG-36N	28" (711)	18-1/2" (470)	14" (356)
USG-42N	34" (864)	22-1/2" (572)	17" (432)
USG-48N	41" (1041)	27-1/4" (692)	20-1/2" (521)

* Values Are After Movement Occurs.

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:

Wabo®GutterFlex

DATE: 01/04/21

MODEL: USG



Watson Bowman Acme
95 Pineview Drive Amherst, NY 14228
phone: (716) 691-7566 fax: (716) 691-9239
www.watsonbowmanacme.com

A brand of **MBCC GROUP**

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:

2

SHEET NO:

2

DRAWING NO:

C-21452