



"WA" Profile
Armored Blockout Condition

Design Features

- Cost effective solutions for general construction
- Over 20 year history of success
- High abrasion and ultra-violet resistance

Model Number	Groove Width "A"						Min. Install Width		Groove Depth "B"		Nominal			
	Min.		Max.		Total		in	mm	in	mm	Width		Height	
	in	mm	in	mm	in	mm					in	mm	in	mm
WA-175	.688	17	1.488	38	.800	20	1.000	25	2.625	67	1.750	44	2.000	51
WA-200	.875	22	1.700	43	.825	21	1.250	32	2.625	67	2.000	51	2.000	51
WA-225	.953	24	1.913	49	.960	24	1.375	35	3.000	76	2.250	57	2.250	57
WA-250	1.000	25	2.125	54	1.125	29	1.500	38	3.563	90	2.500	64	2.500	64
WA-300	1.125	29	2.550	65	1.425	36	1.750	44	4.313	110	3.000	76	3.000	76
WA-350	1.375	35	2.975	76	1.600	41	2.250	57	4.438	113	3.500	89	3.500	89
WA-400	1.625	41	3.400	86	1.775	45	2.500	64	5.000	127	4.000	102	4.000	102
WA-500	1.687	43	4.250	108	2.563	65	3.000	76	5.938	151	5.000	127	5.000	127

PROJECT NAME: _____

PROJECT LOCATION: _____

DRAWING DESCRIPTION:
Wabo®CompressionSeal

DATE: 01/27/2021 MODEL: WA



Watson Bowman Acme
95 Pineview Drive Amherst, NY 14228
phone: (716) 691-7566 fax: (716) 691-9239
www.watsonbowmanacme.com

A brand of
MBCC GROUP

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:
1

SHEET NO:
2

DRAWING NO:
C-20513