



Typical Section

Wall to Wall

Typical Section

Wall to Wall (Corner)

Dimension Chart										
Model	Joint Opening (J.O.)						Total movement		S.W.	
	at install		allow min.		allow max.		at install		at install	
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm
CWWS-400	4	102	2	51	6	152	4	102	4	102
CWWS-500	5	127	2 1/2	64	7 1/2	191	5	127	5	127
CWWS-600	6	152	3	76	9	229	6	152	6	152
CWWS-400C	4	102	2	51	6	152	4	102	4	102
CWWS-500C	5	127	2 1/2	64	7 1/2	191	5	127	5	127
CWWS-600C	6	152	3	76	9	229	6	152	6	152

Note: J.O. minimum and maximum values are after thermal movement occurs.

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:

Wabo®CorridorWrap

DATE: 01/12/2021

MODEL: CWWS



Watson Bowman Acme
 95 Pineview Drive Amherst, NY 14228
 phone: (716) 691-7566 fax: (716) 691-9239
 www.watsonbowmanacme.com

A brand of **MBCC GROUP**

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:

SHEET NO:

1

DRAWING NO:

C21134