



**STANDARD VERTICAL OFFSET DETAIL**  
TYP. SECTION

- Step #1 Locate area of offset repair and mark.
- Step #2 Determine amount of Off Set between opposing slabs
- Step #3 Prepare low side of block-out as required to properly install new repair / leveling material
- Step #4 Mix and install new repair /leveling material as selected material. Note: Wabo®Crete will provide quicker turn around time.
- Step #5 Determine amount of taper required for proper slope based on offset differential
- Step #6 Cut minimum ¼” deep keyway and prepare slab as required to place new Wabo®Crete® Parking Series Elastomeric Concrete to new tapered section.
- Step #7 Mix and apply WBA Wabo®Crete Bonding agent to all adjacent surfaces to receive Wabo®Crete® Parking Series Elastomeric Concrete, as per Manufacturer guidelines ( concrete , asphalt and Cementous repair material). \*Note: Steel not requiring bonding agent.
- Step #8 Mix and install WBA Wabo®Crete® Parking Series Elastomeric Concrete into area of wet bonding agent placement, not allowing bonding agent to cure. “wet Wabo®Crete® Parking Series Elastomeric Concrete to wet Bonding agent.”
- Step #9 Broadcast MasterSeal 940 granules onto all new Wabo®Crete Header material. See Manufacture's Installation Guide for more information.
- Step #10 Allow Wabo®Crete® Parking Series Elastomeric Concrete to cure as per manufacturers guidelines

PROJECT NAME: -
PROJECT LOCATION: -
DRAWING DESCRIPTION:  <b>Wabo®CreteMembrane Gen II</b>
DATE: 02/18/2021



Watson Bowman Acme  
95 Pineview Drive Amherst, NY 14228  
phone: (716) 691-7566 fax: (716) 691-9239  
www.watsonbowmanacme.com

A brand of  
**MBCC GROUP**

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO: 1
SHEET NO: 1
DRAWING NO: A34685