

Wabo[®]CreteStripSeal (Model:SSS) DETAIL

Notes:

1.) Please contact WBA for information on splices, terminations, transitions, and additional details concerning adjacent construction.

2.) Minimum and maximum values shown on dimension chart are the limits for proper system performance. Unless otherwise noted, the dimension shown at "A" Mid is the recommended installation joint opening.

3.) The system and all mechanical components are supplied to accommodate 20 foot section lengths. If required, please consult with a WBA representative for the types and quantities of any chemical components needed for proper installation.

4) Coverplate recommended for "SE" style seals where pedestrian traffic is expected. Contact WBA for additional information.

SLAB TO SLAB CONDITION NOT TO SCALE

() - DENOTES MILLIMETERS

DIMENSION CHART							
PROFILE	MODEL	"A" @ MIN	"A" @ MID	"A" @ MAX	Total Movement		
\sim	SE-800	1/2"(13)	4-1/2"(114)	8-1/2"(216)	8"(203)		

PROJECT NAME: 		Watson Bowman Acme	Watson Bowman Acme 95 Pineview Drive Amherst, NY 14228 phone: (716) 691-7566 fax: (716) 691-9239 www.watsonbowmanacme.com		REVISION NO: 1 SHEET NO:	
DRAWING DESCRIPTION:						
Wabo®CreteStripSeal		strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.				