



Wabo®Flex

SR 2A and SR 2.5A

Design Features

- Exposed riding surfaces are designed w/ aluminum skid resistant plates
- Low profile system
- Designed to prevent debris build-up and allow for a smooth ride

Blockout Dimension Table

Model Number	A		"B"		"C"		"D"		"E"							
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.						
SR 2A	10.125	257	12.125	308	7.375	187	9.375	238	1.000	25	3.00	76	1.375	35	1.813	46
SR 2.5A	13.000	330	15.500	394	9.750	248	12.250	311	1.375	35	3.875	98	1.625	41	2.063	52

Consult your WBA Representative with your special design requirements.

PROJECT NAME: _____

PROJECT LOCATION: _____

DRAWING DESCRIPTION:

Wabo®Flex

DATE: 01/29/2021

MODEL: SR



Watson Bowman Acme
95 Pineview Drive Amherst, NY 14228
phone: (716) 691-7566 fax: (716) 691-9239
www.watsonbowmanacme.com

A brand of
MBCC GROUP

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:

1

SHEET NO:

1

DRAWING NO:

C-20524