



Wabo®Flex

SR 4A - SR 13

Design Features

- Exposed riding surfaces are designed w/ aluminum skid resistant plates
- Accommodates up to 13" of movement
- Low profile system
- Designed to prevent debris build-up and allow for a smooth ride

Blockout Dimension Table

Model Number	A		B				C				D		E			
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.		
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm		
SR 4A	21.500	546	25.500	648	17.625	448	21.625	549	1.000	25	5.000	127	1.938	49	2.375	60
SR 6.5A	25.250	641	31.750	806	21.000	533	27.500	699	1.500	38	8.000	203	2.125	54	3.250	83
SR 9	33.375	848	42.375	1076	29.000	737	38.000	965	1.750	44	10.750	273	2.188	56	4.000	102
SR13	49.000	1245	62.000	1575	43.500	1105	56.500	1435	2.000	51	15.000	381	2.750	70	5.250	133

Consult your WBA Representative with your special design requirements.

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:

Wabo®Flex

DATE: 01/29/2021

MODEL: SR



Watson Bowman Acme
 95 Pineview Drive Amherst, NY 14228
 phone: (716) 691-7566 fax: (716) 691-9239
 www.watsonbowmanacme.com

A brand of
MBCC GROUP

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:

1

SHEET NO:

2

DRAWING NO:

C-20524