



Min. Ø3/8" X 2" lg.  
Redi-Bolt, zinc plated steel,  
concrete expansion anchor,  
12" O.C.(use 3/8" drill)

2 1/2" [64] Min

"J.O."

Vertical Movement  
Upwards - 0"  
Downwards - 1-1/2"

**"HDH" Cover**  
Floor to Floor Condition

Model	"W"	"SW"	J.O. Min	J.O. Mid	J.O. Max	Total Movement	Max Point Load (Mid)	Distributed Load
HDH-200	3 1/2"(89)	8"(203)	1"(25)	2"(51)	3"(76)	2"(51)	550 lbs	300 psi
HDH-300	6 9/16"(166)	13 1/8"(333)	1"(25)	3"(76)	6"(152)	5"(127)	350 lbs	150 psi
HDH-600	9 13/16"(249)	16 3/8"(416)	1"(25)	6"(152)	9"(229)	8"(203)	400 lbs	60 psi

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:

**Wabo®HingeMount**

DATE: 02/01/2020

MODEL: HDH



Watson Bowman Acme  
95 Pineview Drive Amherst, NY 14228  
phone: (716) 691-7566 fax: (716) 691-9239  
www.watsonbowmanacme.com

A brand of  
**MBCC GROUP**

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:

1

SHEET NO:

1

DRAWING NO:

C20435