

ARMORED CONDITION

SLAB-TO-SLAB CONDITION

() - Denotes Millimeters

Nominal Relaxed Dimensions			Movement Range			
Model	"A"	"B"	J.O. Min.	"C"	J.O. Max.	Total Movement
25W	1"(25)	1 1/4"(32)	1/2"(13)	1/4"(6)	1-1/2"(38)	1"(25)
40W	1 5/8"(41)	2 1/4"(57)	3/4"(19)	1/4"(6)	2 1/4"(57)	1 1/2"(38)
50W	2"(51)	2-3/4"(70)	1"(25)	1/4"(6)	3"(76)	2"(51)
65W	2 1/2"(64)	3 3/8"(86)	1 1/4"(32)	1/4"(6)	3 3/4"(95)	2 1/2"(65)
75W	3"(76)	3 7/8"(100)	1 1/2"(38)	1/4"(6)	4 1/2"(114)	3"(76)
100W	4"(102)	5 1/8"(129)	2"(51)	1/4"(6)	6"(152)	4"(102)

PROJECT NAME:

PROJECT LOCATION

DRAWING DESCRIPTION

Wabo®Jeene

Watson Bowman Acme 95 Pineview Drive Amherst, NY 14228 phone: (716) 691-7566 fax: (716) 691-9239 www.watsonbowmanacme.com

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is

strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are

provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All



3 DRAWING NO:

1

REVISION NO

SHEET NO:

C-96011

DATE: 01/28/2021

MODEL: W

Watson Bowman

Acme

technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.