

1.) Please refer to the installation guide for information on splices, terminations, and transitions.

2.) Minimum and maximum values shown on dimension chart are the limits for proper system performance.

Max. Joint	Min. Installation	Movement
nening "A"		Pating (MP)

	Rec. Min.	Min. Joint	Max. Joint	Min. Installation	Movement
Model	Install. Width	Opening "A"	Opening "A"	Depth "B"	Rating (MR)
Wabo®SPS-500	2"(51)	1-1/2"(38)	6.5"(165)	4-3/4"(121)	5"(127)

PROJECT NAME: DRAWING DESCRIPTION

Watson Bowman Acme

Watson Bowman Acme 95 Pineview Drive Amherst, NY 14228 phone: (716) 691-7566 fax: (716) 691-9239 www.watsonbowmanacme.com

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is

**MBCC** GROUP

SHEET NO:

DRAWING NO: A-34373

REVISION NO

() - Denotes Millimeters

strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

DATE: 01/27/2021 MODEL: SPS-500

Wabo®SPS Joint System