



NBW-400 thru NBW-2400

Notes:

1. Exposed Aluminum Surfaces to be Class II Clear Anodized.
2. Proper location of studs required to secure expansion joint system to wall. Consult WBA prior to wall construction to ensure proper stud locations. Locations vary by model and size of system.

Dimension Chart

Model	"A" Min	"A" Mid	"A" Max	SW @ "A" Mid	Total Seismic Movement
NBW-400	2"(51)	4"(102)	6"(152)	11 7/8"(302)	4"(102)
NBW-600	2"(51)	6"(152)	9"(229)	15 7/8"(403)	7"(178)
NBW-800	2"(51)	8"(203)	12"(305)	17 7/8"(454)	10"(254)
NBW-1000	2"(51)	10"(254)	15"(381)	21 7/8"(556)	13"(330)
NBW-1200	2"(51)	12"(305)	18"(457)	23 7/8"(606)	16"(406)
NBW-1800	2"(51)	18"(457)	27"(686)	33 3/8"(848)	25"(635)
NBW-2400	2"(51)	24"(610)	36"(914)	42 3/8"(1076)	34"(864)

PROJECT NAME:

PROJECT LOCATION:

DRAWING DESCRIPTION:

WaboSeisMaxPlus II Wall

DATE: 03/08/2021

MODEL: NBW



Watson Bowman Acme
95 Pineview Drive Amherst, NY 14228
phone: (716) 691-7566 fax: (716) 691-9239
www.watsonbowmanacme.com

A brand of
MBCC GROUP

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:

SHEET NO:

DRAWING NO:

S10008