



Typical Section
Floor To Floor

- NOTE:
1. TOTAL THERMAL MOVEMENT CAPABILITY OF 2 COMPONENT POLYURETHANE SEALANT IS 1 1/4" (TYPICAL ALL MODEL SIZES)
 2. ENHANCED MOVEMENT CAPABILITIES AVAILABLE.

NOTE: EXPOSED ALUMINUM SURFACES MILL FINISH (STANDARD).

Model	Joint Opening (J.O.)						Total Seismic Movement		S.W.		B (min)	
	at install		allow min.		allow max.				at install			
	inches	mm	inches	mm	inches	mm	inches	mm	inches	mm		
SPJ-400	4	100	1 1/4	32	6	152	4 3/4	121	12 7/8	327	6	152
SPJ-600	6	152	1 1/4	32	9	229	7 3/4	197	14 7/8	378	6	152

Note: J.O. minimum and maximum values are after seismic movement occurs.

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:
Wabo®SeismicPan

DATE: 05/17/2021 MODEL: SPJ



Watson Bowman Acme
95 Pineview Drive Amherst, NY 14228
phone: (716) 691-7566 fax: (716) 691-9239
www.watsonbowmanacme.com

A brand of
MBCC GROUP

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO: -

SHEET NO: 2

DRAWING NO: C18331