



- Designated to prevent debris build-up and allow for a smooth ride
- Low profile system
- Accommodates up to 13" of movement

Design Features

Model	"A"		"B"		"C"		"D"	
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.
	inches	mm	inches	mm	inches	mm	inches	mm
400A	21 1/4	540	25 1/4	641	17 5/8	448	2 1/8	54
650	25 1/4	641	31 3/4	806	21	533	3	76
900	30 7/8	784	39 7/8	1013	26 1/2	673	3 3/4	95
1300	41	1041	54	1372	36	914	5	127

PROJECT NAME: _____

PROJECT LOCATION: _____

DRAWING DESCRIPTION: _____

Waboo® TransFlex

DATE: 04/22/24 MODEL: 400A-1300



Watson Bowman Acme
 95 Pineview Drive Amherst, NY 14228
 phone: (716) 691-7566 fax: (716) 691-9239
 www.watsonbowmanacme.com



Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation, ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO: 3

SHEET NO: 1

DRAWING NO: C21395