



Typical Section

Model	Dimension Chart								S.W.	
	Joint Opening (J.O.)						Total movement		at install	
	at install		allow min.		allow max.					
inches	mm	inches	mm	inches	mm	inches	mm	inches	mm	
TSF-200C	2	51	1 1/8	29	3 5/8	92	2 1/2	64	4 7/8	124
TSF-400C	4	102	1 1/8	29	5 5/8	143	4 1/2	114	6 7/8	175
TSF-600C	6	152	1 1/8	29	7 5/8	194	6 1/2	165	8 7/8	225

Note: J.O. minimum and maximum values are after seismic movement occurs.

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:

Wabo®TwinSeam Wall

DATE: 05/2021

MODEL: TSF-C



Watson Bowman Acme  
 95 Pineview Drive Amherst, NY 14228  
 phone: (716) 691-7566 fax: (716) 691-9239  
 www.watsonbowmanacme.com

A brand of  
**MBCC GROUP**

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:  
-

SHEET NO:  
2

DRAWING NO:  
C21045