Aluminum Cente Profile		ograph Seismic rol Mechanism	Spa (Op	4" Self-tapping Screw aced at 18" (457) O.C. otional Plastic insert for sonry Construction)	
			-1	^{6.4)} um Edge Profile eric Visual Seal	
	INTERIOR APP High-strength Nylon Components With Threaded Inserts			() - Denote	s Millimeters
		PLAN VIEW PH CONTROL MECHANISM	DIM MODEL "A" at Min WSW-900 4 1/8"(105) WSW-1500 6"(152) WSW-1800 6"(152) * Designed Without Stress T Wider Movement During S	15"(381) 26 1/4"(667) 18"(457) 34 1/2"(876) To The System Components	28 1/2"(724)
PROJECT NAME: - PROJECT LOCATION: - DRAWING DESCRIPTION: Wabo®WeatherSeam DATE: 01/25/2021 MOD	Watson Bowman Acme Corporati strictly prohibited, except for the provided by Company for informatio	Watson Bown 95 Pineview Drive Ar phone: (716) 691-7566 www.watsonbown ding but not limited to, any drawing, design, photog on ("Company"). Reproduction, translation, or red express purpose for which it has been furnished, on purposes only. Company reserves the right to a ny, whether verbal or written, concerning products is used at the Use	mherst, NY 14228 fax: (716) 691-9239 manacme.com graph, graphic, or statement(s) ("Materials") duction to any electronic medium or machine without prior written consent of Company. A amend or withdraw any information containe s, or the use of products in specific situations	readable form, in whole or part, is All Materials contained herein are d in the Materials without notice. All	REVISION NO: 1 SHEET NO: 4 DRAWING NO: C-95021

Б