## LEED v4 & 4.1 Wabo®CreteMembrane



LEED® BD+C: NC, CS, SCHOOLS, RETAIL, DATA CENTERS, WAREHOUSES & DISTRIBUTION CENTERS, HOSPITALITY, HEALTHCARE				
CSI Division	07 95 00	Product Manufacturer	Watson Bowman Acme	
Product Name	Wabo®CreteMembrane			
Product Description	Wabo®Crete Membrane (ME, MM, MX) is the industry's original and most-specified elastomeric concrete system. It has a proven history as a high performance joint sealing system specifically designed to meet the unique demands of parking structures and stadiums.			
System Components	Instillation materials listed below			

Recycled Content Pre-consumer Post-consumer	Pre	Post
	0%	0%

Indoor Environmental Quality (EQ) Credits	Low-Emitting Materials: VOC emissions evalua	ation	California Department of Public Heal Emisions Test* availability	th (CDPH) v1.2	No
Indoor Environmental Quality (EQ) Credits	Low-Emitting Materials: VOC content	Has a ' conten	Volatile Organic Compound (VOC) t of	(See component chart below)	Yes

VOC emissions evaluations follow guidance from: California Department of Public Health (CDPH) standard method V1.2-2017 and complies with limits in Table 4-1 of the method; VOC content evaluation follow: Adhesives and Sealants: SCAQMD Rule 1168 effective October 6, 2017, OR Paints and Coatings: CARB 2007 (SCM) for Architectural Coatings and (SCAQMD) Rule 1113, effective February 5, 2016

COMPONENT CHART	INDOOR ENVIRONMENTAL QUALITY (EQ) CREDITS
Components:	Low-Emitting Materials: VOC content evaluation
Elastomeric Header Material	When components are mixed: WaboCrete is < or = 50 g/L
Part A	0 g/L
Part B	26.74 g/L
Part C -agg	0 g/L
MasterSeal 940	0 g/L

Respectfully, LEED Administrator Tel: 1-800-677-4922



"LEED" is a trademark of the U.S. Green Building Council

**Watson Bowman Acme** 95 Pineview Drive Amherst, NY 14228

A brand of

**MBCC** GROUP

August 24, 2023