

LEED v4 & 4.1

Wabo®FireShield



LEED® BD+C: NC, CS, SCHOOLS, RETAIL, DATA CENTERS, WAREHOUSES & DISTRIBUTION CENTERS, HOSPITALITY, HEALTHCARE

CSI Division	07 95 00	Product Manufacturer	Watson Bowman Acme
Product Name	Wabo®FireShield		
Product Description	Wabo®FireShield is a second generation unified fire rated, sound, energy and waterproof sealant system. It has a 2 or 3hr fire rating in accordance with US-2079 and is listed with USC & UL. The system can accommodate structural movement up to +/-50% and maintain a watertight application.		
System Components	Two options available		

	FSH-HORIZONTAL		FSV-VERTICAL	
Recycled Content Pre-consumer Post-consumer	Pre	Post	Pre	Post
Stainless steel coverplates	0%	0%	0%	0%

Indoor Environmental Quality (EQ) Credits	Low-Emitting Materials: VOC emissions evaluation	California Department of Public Health (CDPH) v1.2 Emissions Test* availability	No	No
Indoor Environmental Quality (EQ) Credits	Low-Emitting Materials: VOC emissions evaluation	Has a Volatile Organic Compound (VOC) content of	(See component chart below)	Yes

VOC emissions evaluations follow guidance from: California Department of Public Health (CDPH) standard method V1.2-2017 and complies with limits in Table 4-1 of the method; VOC content evaluation follow: Adhesives and Sealants: SCAQMD Rule 1168 effective October 6, 2017, OR Paints and Coatings: CARB 2007 (SCM) for Architectural Coatings and (SCAQMD) Rule 1113, effective February 5, 2016

COMPONENT CHART	INDOOR ENVIRONMENTAL QUALITY (EQ) CREDITS
Components:	Low-Emitting Materials: VOC content evaluation
Epoxy adhesive	When components are mixed: Epoxy Adhesive is < or = 5 g/L
Part A	<5 g/L
Part B	<5 g/L
Silicone 888	26 g/L
Sil300	20 g/L
SWS Silicone 790	38.5 g/L

Respectfully,
LEED Administrator
 Tel: 1-800-677-4922



"LEED" is a trademark of the U.S. Green Building Council

Watson Bowman Acme
 95 Pineview Drive
 Amherst, NY 14228

A brand of

MBCC GROUP

August 24, 2023