

WABO URA SEALANT, PART A

Version 1.0 Revision Date: 07/06/2022 SDS Number: 000000260050 Date of last issue: -
Date of first issue: 07/06/2022

SECTION 1. IDENTIFICATION

Product name : WABO URA SEALANT, PART A

Other means of identification : Part #2750

Manufacturer or supplier's details

Company name of supplier : Watson Bowman Acme Corp.

Address : 95 Pineview Drive
Amherst, NY 14228

Emergency telephone : ChemTel: +1-813-248-0585

National Emergency Tele-
phone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Recommended use of the chemical and restrictions on use

Recommended use : Sealant

Restrictions on use : Reserved for industrial and professional use.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Acute toxicity (Oral) : Category 4

Skin irritation : Category 2

Serious eye damage : Category 2A

Specific target organ toxicity : Category 2 (Lung)
- repeated exposure (Inhalation)

GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H319 Causes serious eye irritation.
H315 Causes skin irritation.
H302 Harmful if swallowed.
H373 May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

WABO URA SEALANT, PART A

Version 1.0 Revision Date: 07/06/2022 SDS Number: 000000260050 Date of last issue: -
 Date of first issue: 07/06/2022

Precautionary Statements : **Prevention:**
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P260 Do not breathe dusts or mists.
 P270 Do not eat, drink or smoke when using this product.
 P264 Wash face, hands and any exposed skin thoroughly after handling.

Response:
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P314 Get medical advice/ attention if you feel unwell.
 P302 + P352 IF ON SKIN: Wash with plenty of water.
 P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.

Disposal:
 P501 Dispose of contents/container to appropriate hazardous waste collection point.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|--|------------|-----------------------|
| Solvent naphtha (petroleum), heavy arom. | 64742-94-5 | >= 20 - < 30 |
| talc | 14807-96-6 | >= 10 - < 20 |
| Carbon black | 1333-86-4 | >= 1 - < 5 |

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water

WABO URA SEALANT, PART A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 07/06/2022 | 000000260050 | Date of first issue: 07/06/2022 |

- and soap.
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.
- In case of eye contact : Remove contact lenses, if present.
Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.
- If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do NOT induce vomiting.
- Most important symptoms and effects, both acute and delayed : Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
May cause damage to organs through prolonged or repeated exposure if inhaled.
- Notes to physician : Treat symptomatically.
-

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Foam
Water spray
Dry powder
Carbon dioxide (CO₂)
- Unsuitable extinguishing media : water jet
- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.
If exposed to fire, keep containers cool by spraying with water.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protection : Do not breathe vapour/aerosol/spray mists.
-

WABO URA SEALANT, PART A

Version 1.0 Revision Date: 07/06/2022 SDS Number: 000000260050 Date of last issue: -
 Date of first issue: 07/06/2022

- tive equipment and emergency procedures Wear eye/face protection.
 If exposed to high vapour concentration, leave area immediately.
 Use personal protective clothing.
 Handle in accordance with good building materials hygiene and safety practice.
- Environmental precautions : Contain contaminated water/firefighting water.
 Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.
 Pick up with inert absorbent material (e.g. sand, earth etc.).
 Spilled product should be disposed in accordance with all applicable government regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid aerosol formation.
 Avoid inhalation of mists/vapours.
 Avoid skin contact.
 Avoid contact with eyes.
- Conditions for safe storage : Store in original container.
 Keep in a dry, cool and well-ventilated place.
 Protect from direct sunlight.
 Keep away from sources of ignition - No smoking.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--|------------|--------------------------------|---|-----------|
| Solvent naphtha (petroleum), heavy arom. | 64742-94-5 | TWA value (Non-aerosol) | 200 mg/m ³ (total hydrocarbon vapor) | ACGIHTLV |
| | | Skin Designation (Non-aerosol) | | ACGIHTLV |
| | | REL value | 100 mg/m ³ | NIOSH |
| | | TWA | 200 mg/m ³ (total hydrocarbon vapor) | ACGIH |
| talc | 14807-96-6 | TWA (Dust) | 20 Million particles per cubic foot | OSHA Z-3 |
| | | TWA (respirable dust fraction) | 2 mg/m ³ | OSHA P0 |
| | | TWA (Respirable) | 2 mg/m ³ | NIOSH REL |
| | | TWA | 0.1 fibres per | ACGIH |

WABO URA SEALANT, PART A

Version 1.0 Revision Date: 07/06/2022 SDS Number: 000000260050 Date of last issue: -
 Date of first issue: 07/06/2022

| | | | | |
|--------------|-----------|-------------------------------------|---------------------------------|-----------|
| | | | cubic centimeter | |
| | | TWA (Respirable particulate matter) | 2 mg/m ³ | ACGIH |
| Carbon black | 1333-86-4 | TWA (Inhalable particulate matter) | 3 mg/m ³ | ACGIH |
| | | TWA | 3.5 mg/m ³ | NIOSH REL |
| | | TWA | 3.5 mg/m ³ | OSHA Z-1 |
| | | TWA | 3.5 mg/m ³ | OSHA P0 |
| | | TWA | 0.1 mg/m ³ (PAHs) | NIOSH REL |

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.
 Use NIOSH approved respiratory protection.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Tightly fitting safety goggles (chemical goggles).

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Do not inhale gases/vapours/aerosols.
 Avoid contact with the skin, eyes and clothing.
 Avoid exposure - obtain special instructions before use.
 Handle in accordance with good building materials hygiene and safety practice.
 Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.
 Hands and/or face should be washed before breaks and at the end of the shift.
 At the end of the shift the skin should be cleaned and skin-care agents applied.
 Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
 Gloves must be inspected regularly and prior to each use.
 Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

WABO URA SEALANT, PART A

Version 1.0 Revision Date: 07/06/2022 SDS Number: 000000260050 Date of last issue: -
Date of first issue: 07/06/2022

Color : black

Odor : aromatic

Odor Threshold : not determined

pH : Not applicable

Freezing point : Not applicable

Boiling point : > 450 °F / > 232 °C

Flash point : > 199.9 °F / > 93.3 °C

Evaporation rate : No data available

Flammability (liquids) : Not classified as a flammability hazard

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : Not applicable

Relative vapor density : No data available

Relative density : 1.16

Density : No data available

Solubility(ies)
Water solubility : slightly soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : not applicable for mixtures

Autoignition temperature : Not applicable

Decomposition temperature : No decomposition if stored and handled as prescribed/indicated.

Viscosity
Viscosity, dynamic : 10,000 cps

Viscosity, kinematic : No data available

WABO URA SEALANT, PART A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 07/06/2022 | 000000260050 | Date of first issue: 07/06/2022 |

| | | |
|----------------------|---|-------------------|
| Explosive properties | : | Not explosive |
| Oxidizing properties | : | No data available |
| Sublimation point | : | No data available |
| Molecular weight | : | Not applicable |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|--|
| Reactivity | : | No hazardous reactions if stored and handled as prescribed/indicated. |
| Chemical stability | : | The product is stable if stored and handled as prescribed/indicated. |
| Possibility of hazardous reactions | : | The product is stable if stored and handled as prescribed/indicated. |
| Conditions to avoid | : | See SDS section 7 - Handling and storage. |
| Incompatible materials | : | Strong acids Strong bases Strong oxidizing agents Strong reducing agents |
| Hazardous decomposition products | : | No hazardous decomposition products if stored and handled as prescribed/indicated. |

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Harmful if swallowed.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

WABO URA SEALANT, PART A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 07/06/2022 | 000000260050 | Date of first issue: 07/06/2022 |

| | | |
|-------------|---|-----------|
| IARC | Group 2B: Possibly carcinogenic to humans Carbon black | 1333-86-4 |
|-------------|---|-----------|

Reproductive toxicity

Not classified based on available information.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

Product:

No aspiration hazard expected.

Further information**Product:**

Remarks : Health injuries are not known or expected under normal use. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

WABO URA SEALANT, PART A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 07/06/2022 | 000000260050 | Date of first issue: 07/06/2022 |

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

SECTION 14. TRANSPORT INFORMATION

International Regulations**UNRTDG**

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

Not regulated as a dangerous good

Special precautions for user

Not applicable

SECTION 15. REGULATORY INFORMATION

US State Regulations**Pennsylvania Right To Know**

| | |
|--|------------|
| Solvent naphtha (petroleum), heavy arom. | 64742-94-5 |
| talc | 14807-96-6 |
| Carbon black | 1333-86-4 |

New Jersey Right To Know

| | |
|--------------|------------|
| talc | 14807-96-6 |
| Carbon black | 1333-86-4 |

California Prop. 65

WARNING: This product can expose you to chemicals including Carbon black, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

WABO URA SEALANT, PART A

Version 1.0 Revision Date: 07/06/2022 SDS Number: 000000260050 Date of last issue: -
 Date of first issue: 07/06/2022


The ingredients of this product are reported in the following inventories:

- TSCA : All substances listed as active on the TSCA inventory
- DSL : All components of this product are on the Canadian DSL


SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

- ACGIH : USA. ACGIH Threshold Limit Values (TLV)
- ACGIHTLV : American Conference of Governmental Industrial Hygienists - threshold limit values (US)
- NIOSH : NIOSH Pocket Guide to Chemical Hazards (US)
- NIOSH REL : USA. NIOSH Recommended Exposure Limits
- OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
- OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
- OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
- ACGIH / TWA : 8-hour, time-weighted average
- ACGIHTLV / Skin Designation : Skin Designation:
- ACGIHTLV / TWA value : Time Weighted Average (TWA):
- NIOSH / REL value : Recommended exposure limit (REL):
- NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
- OSHA P0 / TWA : 8-hour time weighted average
- OSHA Z-1 / TWA : 8-hour time weighted average
- OSHA Z-3 / TWA : 8-hour time weighted average

WABO URA SEALANT, PART A

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: - |
| 1.0 | 07/06/2022 | 000000260050 | Date of first issue: 07/06/2022 |

AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 07/06/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN