

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

### SECTION 1. IDENTIFICATION

Product name : WABO PRIMALUB ADHESIVE

Product code : 000000000051273620

Other means of identification : Part #2720

#### Manufacturer or supplier's details

Company name of supplier : Watson Bowman Acme Corp.

Address : 95 Pineview Drive  
Amherst, NY 14228

Emergency telephone : ChemTel: +1-813-248-0585

National Emergency Tele-  
phone Number : Canada: 1-800-255-3924 ChemTel contract no. MIS9240420

#### Recommended use of the chemical and restrictions on use

Recommended use : Adhesives and/or sealants

Restrictions on use : Reserved for industrial and professional use.

---

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with the Hazardous Products Regulations

Flammable liquids : Category 3

Aspiration hazard : Category 1

Acute toxicity (Inhalation) : Category 4

Skin corrosion/irritation : Category 2

Eye irritation : Category 2B

Respiratory sensitization : Category 1

Skin sensitization : Category 1B

Germ cell mutagenicity : Category 1B

Carcinogenicity : Category 1B

Specific target organ toxicity : Category 3 (Respiratory system, Central nervous system)  
- single exposure

Specific target organ toxicity : Category 1 (Central nervous system)

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

- repeated exposure

Short-term (acute) aquatic hazard : Category 3

Long-term (chronic) aquatic hazard : Category 3

### GHS label elements

Hazard pictograms :



Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.  
H315 + H320 Causes skin and eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H304 May be fatal if swallowed and enters airways.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H350 May cause cancer.  
H340 May cause genetic defects.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.  
H402 Harmful to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P271 Use only outdoors or in a well-ventilated area.  
P201 Obtain special instructions before use.  
P260 Do not breathe dusts or mists.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist.  
P202 Do not handle until all safety precautions have been read and understood.  
P273 Avoid release to the environment.  
P243 Take action to prevent static discharges.  
P284 In case of inadequate ventilation wear respiratory protection.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ .? / equipment.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version 1.0      Revision Date: 04/19/2022      SDS Number: 000000260428      Date of last issue: -  
Date of first issue: 04/19/2022

P242 Use only non-sparking tools.  
P240 Ground and bond container and receiving equipment.

### Response:

P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.

### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.  
P233 Keep container tightly closed.  
P405 Store locked up.

### Disposal:

P501 Dispose of contents/container to appropriate hazardous waste collection point.

### Other hazards

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Isocyanates  
solvent(s)

### Components

Chemical name	Common Name/Synonym	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), light arom.	Light aromatic solvent naphtha	64742-95-6	$\geq 10 - < 15$
Distillates (petroleum), hydrotreated light	Hydrotreated light distillates (petroleum)	64742-47-8	$\geq 7 - < 15$
Diphenylmethane-4,4'-diisocyanate (MDI)	MDI	101-68-8	$\geq 7 - < 10$
Stoddard solvent	Stoddard solvent	8052-41-3	$\geq 3 - < 10$
Methylenediphenyl diisocyanate	Benzene, 1,1'-methylenebis[isocyanato-	26447-40-5	$\geq 3 - < 5$
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	P-MDI	9016-87-9	$\geq 3 - < 5$

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version 1.0      Revision Date: 04/19/2022      SDS Number: 000000260428      Date of last issue: -  
Date of first issue: 04/19/2022

Silicon dioxide	Silica	7631-86-9	$\geq 1 - < 5$
disodium oxide	Sodium oxide (Na <sub>2</sub> O)	1313-59-3	$\geq 0.2 - < 1$
Titanium dioxide	C.I. Pigment White 6	13463-67-7	$\geq 0.3 - < 1$
Nonane	n-Nonane	111-84-2	$\geq 0.1 - < 1$
dipotassium oxide	Potassium oxide (K <sub>2</sub> O)	12136-45-7	$\geq 0.1 - < 0.2$
Polymethylene poly-phenylisocyanate, polyethylene glycol polymer	Isocyanic acid, polymethylene-polyphenylene ester, polymer with $\alpha$ -hydro- $\omega$ -hydroxy-poly(oxy-1,2-ethanediyl)	57636-09-6	$\geq 0.1 - < 0.2$

### SECTION 4. FIRST AID MEASURES

- General advice : First aid personnel should pay attention to their own safety.  
Remove contaminated clothing.
- If inhaled : Remove the affected individual into fresh air and keep the person calm.  
Assist in breathing if necessary.  
Immediate medical attention required.
- In case of skin contact : Wash affected areas thoroughly with soap and water.  
If irritation develops, seek medical attention.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
Immediate medical attention required.
- If swallowed : Rinse mouth and then drink 200-300 ml of water.  
Do NOT induce vomiting.  
Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.  
Immediate medical attention required.
- Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.  
Causes skin and eye irritation.  
May cause an allergic skin reaction.  
Harmful if inhaled.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause genetic defects.  
May cause cancer.  
Causes damage to organs through prolonged or repeated

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

exposure.

Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	: High volume water jet
Hazardous combustion products	: nitrous gases fumes/smoke isocyanate vapor
Further information	: Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.
Special protective equipment for fire-fighters	: Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	: Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment. Avoid contact with the skin, eyes and clothing. Avoid all sources of ignition: heat, sparks, open flame.
Environmental precautions	: Prevent spread over a wide area (e.g. by containment or oil barriers). Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Move container to a well-ventilated area (outside). Spill area can be decontaminated with the following recommended decontamination solution: Mixture of 90 % water, 5-8 % household ammonia, 2-5 % detergent. Add at a 10 to 1 ratio. Allow solution to stand for at least 10 minutes.

---

### SECTION 7. HANDLING AND STORAGE

Advice on protection against	: Sources of ignition should be kept well clear.
------------------------------	--

---

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

- fire and explosion      Take precautionary measures against static discharges.  
Substance/product can form explosive mixture with air.  
Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.
- Advice on safe handling      :    Provide suitable exhaust ventilation at the processing machines.  
Ensure thorough ventilation of stores and work areas.  
Avoid aerosol formation.  
Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
When handling heated product, vapours of the product should be ventilated, and respiratory protection used.  
Wear respiratory protection when spraying.  
Danger of bursting when sealed gastight.  
If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.  
Protect against moisture.
- Conditions for safe storage      :    Keep away from sources of ignition - No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage conditions      :    Keep container tightly closed and in a well-ventilated place.  
Keep away from heat.  
Avoid all sources of ignition: heat, sparks, open flame.
- Recommended storage temperature      :    10 - 32 °C
- Further information on storage stability      :    Protect from direct sunlight.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA value (Non-aerosol)	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIHTLV
		Skin Designation (Non-aerosol)		ACGIHTLV
		REL value	100 mg/m <sup>3</sup>	NIOSH

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version 1.0      Revision Date: 04/19/2022      SDS Number: 000000260428      Date of last issue: -  
Date of first issue: 04/19/2022

		TWA	200 mg/m3 (total hydrocarbon vapor)	CA BC OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
		TWA (Mist)	5 mg/m3	CA AB OEL
		STEL (Mist)	10 mg/m3	CA AB OEL
		TWAEV (Mist)	5 mg/m3	CA QC OEL
		STEV (Mist)	10 mg/m3	CA QC OEL
		TWA	525 mg/m3	CA ON OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	200 mg/m3 (total hydrocarbon vapor)	CA AB OEL
		TWA	200 mg/m3 (total hydrocarbon vapor)	ACGIH
Diphenylmethane-4,4'- diisocyanate (MDI)	101-68-8	TWA	0.005 ppm 0.05 mg/m3	CA AB OEL
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
		TWA	0.005 ppm	CA ON OEL
		C	0.02 ppm	CA ON OEL
		TWAEV	0.005 ppm 0.051 mg/m3	CA QC OEL
		TWA	0.005 ppm	ACGIH
Stoddard solvent	8052-41-3	TWA value	100 ppm	ACGIH TLV
		REL value	350 mg/m3	NIOSH
		Ceil_Time	1,800 mg/m3	NIOSH
		PEL	500 ppm 2,900 mg/m3	29 CFR 1910.1000 (Table Z-1)
		TWA value	100 ppm 525 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	100 ppm 572 mg/m3	CA AB OEL
		TWA	290 mg/m3	CA BC OEL
		STEL	580 mg/m3	CA BC OEL
		TWAEV	100 ppm 525 mg/m3	CA QC OEL
		TWA	525 mg/m3	CA ON OEL
		TWA	100 ppm	ACGIH
Methylenediphenyl diisocya- nate	26447-40-5	TWAEV	0.005 ppm 0.051 mg/m3	CA QC OEL
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
Silicon dioxide	7631-86-9	TWA (Res- pirable par-	0.025 mg/m3 (Silica)	CA AB OEL

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version 1.0      Revision Date: 04/19/2022      SDS Number: 000000260428      Date of last issue: -  
Date of first issue: 04/19/2022

		ticulates)		
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9	TWA	0.005 ppm 0.07 mg/m3	CA AB OEL
		TWAEV	0.005 ppm 0.051 mg/m3	CA QC OEL
		TWA	0.005 ppm	CA BC OEL
		C	0.01 ppm	CA BC OEL
Nonane	111-84-2	REL value	200 ppm 1,050 mg/m3	NIOSH
		TWA value	200 ppm 1,050 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
		TWA	200 ppm 1,050 mg/m3	CA AB OEL
		TWA	200 ppm	CA BC OEL
		TWAEV	200 ppm 1,050 mg/m3	CA QC OEL
		TWA	200 ppm	ACGIH

**Engineering measures** : Ensure adequate ventilation.

### Personal protective equipment

**Respiratory protection** : When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.  
For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

**Hand protection**

**Remarks** : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Safety glasses with side-shields.

**Skin and body protection** : Body protection must be chosen based on level of activity and exposure.  
Antistatic apron

**Protective measures** : Do not inhale gases/vapours/aerosols.  
Avoid contact with the skin, eyes and clothing.  
Avoid exposure - obtain special instructions before use.  
Handle in accordance with good building materials hygiene and safety practice.  
Wearing of closed work clothing is recommended.  
Wear protective clothing as necessary to prevent contact.  
Eye wash fountains and safety showers must be easily ac-



# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version 1.0	Revision Date: 04/19/2022	SDS Number: 000000260428	Date of last issue: - Date of first issue: 04/19/2022
----------------	------------------------------	-----------------------------	--

---

cessible.  
Observe the appropriate PEL or TLV value.

Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).  
Wash soiled clothing immediately.  
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.

---

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: light gray
Odor	: aromatic
Odor Threshold	: not determined
pH	: Not applicable
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 100 °C
Flash point	: 42 °C
Evaporation rate	: No data available
Flammability (liquids)	: Flammable liquid and vapor.
Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapor pressure	: No data available
Relative vapor density	: No data available
Relative density	: No data available

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

Density	:	1.02 g/cm <sup>3</sup> (20 °C)
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Oxidizing properties	:	Not an oxidizer.
Sublimation point	:	No data available
Molecular weight	:	Not applicable

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	Vapors may form explosive mixture with air.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents
Hazardous decomposition products	:	No hazardous decomposition products if stored and handled as prescribed/indicated.

---

### SECTION 11. TOXICOLOGICAL INFORMATION

**Acute toxicity**  
Harmful if inhaled.

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

### **Product:**

Acute inhalation toxicity : ATE: 3.77 mg/l  
Remarks: Determined for mist

### **Skin corrosion/irritation**

Causes skin irritation.

### **Serious eye damage/eye irritation**

Causes eye irritation.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

#### **Germ cell mutagenicity**

May cause genetic defects.

#### **Carcinogenicity**

May cause cancer.

**IARC** Group 2B: Possibly carcinogenic to humans  
Titanium dioxide

13463-67-7

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT-single exposure**

May cause respiratory irritation.

May cause drowsiness or dizziness.

#### **STOT-repeated exposure**

Causes damage to organs (Central nervous system) through prolonged or repeated exposure.

#### **Aspiration toxicity**

May be fatal if swallowed and enters airways.

#### **Further information**

### **Product:**

Remarks : The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Remarks : Solvents may degrease the skin.

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Product:**

#### **Ecotoxicology Assessment**

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

### Persistence and degradability

No data available

### Bioaccumulative potential

#### Components:

#### Stoddard solvent:

Partition coefficient: n-octanol/water : log Pow: 3.5 - 6.4 (20 °C)  
Method: Partition coefficient (n-octanol/water), HPLC method.

#### Nonane:

Partition coefficient: n-octanol/water : log Pow: 5.65  
Method: other  
GLP: no

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### UNRTDG

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(STODDARD SOLVENT, SOLVENT NAPHTHA)

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

Class : 3  
Packing group : III  
Labels : 3

### IATA-DGR

UN/ID No. : UN 1993  
Proper shipping name : Flammable liquid, n.o.s.  
(STODDARD SOLVENT, SOLVENT NAPHTHA)

Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

### IMDG-Code

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(STODDARD SOLVENT, SOLVENT NAPHTHA)

Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Domestic regulation

### TDG

UN number : UN 1993  
Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(STODDARD SOLVENT, SOLVENT NAPHTHA)

Class : 3  
Packing group : III  
Labels : 3  
ERG Code : 128  
Marine pollutant : no

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## SECTION 15. REGULATORY INFORMATION

### The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : This product contains one or more components not listed on the Canadian DSL or NDSL. All other components are listed on the Canadian DSL or NDSL.

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
CA AB OEL	: Canada. Alberta, Occupational Health and Safety Code (table 2: OEL)
CA BC OEL	: Canada. British Columbia OEL
CA ON OEL	: Ontario Table of Occupational Exposure Limits made under the Occupational Health and Safety Act.
CA QC OEL	: Québec. Regulation respecting occupational health and safety, Schedule 1, Part 1: Permissible exposure values for airborne contaminants
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
ACGIH / TWA	: 8-hour, time-weighted average
ACGIHTLV / Skin Designation	: Skin Designation:
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
CA AB OEL / TWA	: 8-hour Occupational exposure limit
CA AB OEL / STEL	: 15-minute occupational exposure limit
CA BC OEL / TWA	: 8-hour time weighted average
CA BC OEL / STEL	: short-term exposure limit
CA BC OEL / C	: ceiling limit
CA ON OEL / C	: Ceiling Limit (C)
CA ON OEL / TWA	: Time-Weighted Average Limit (TWA)
CA QC OEL / TWA EV	: Time-weighted average exposure value
CA QC OEL / STEV	: Short-term exposure value
NIOSH / Ceil_Time	: Ceiling Limit Value and Time Period (if specified):
NIOSH / REL value	: Recommended exposure limit (REL):

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median

# SAFETY DATA SHEET

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 04/19/2022  
Date format : mm/dd/yyyy

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

CA / EN