

## WABO PRIMALUB ADHESIVE

Version            Revision Date:            SDS Number:            Date of last issue: -  
1.0                04/19/2022                000000260428            Date of first issue: 04/19/2022

---

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name                : WABO PRIMALUB ADHESIVE  
Product code                : 00000000051273620  
Other means of identification : Part #2720

**Manufacturer or supplier's details**

Company name of supplier : Watson Bowman Acme Corp.  
Address                     : 95 Pineview Drive  
                                  Amherst, NY 14228

Emergency telephone        : ChemTel: +1-813-248-0585; Mexico: 800-099-0731; Ciudad  
                                  de México: +55 55591588; 800-00-214-00

**Recommended use of the chemical and restrictions on use**

Recommended use            : Adhesives and/or sealants  
Restrictions on use         : Reserved for industrial and professional use.

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**


Flammable liquids            : Category 3  
Aspiration hazard            : Category 1  
Acute toxicity (Inhalation) : Category 4  
Skin corrosion/irritation    : Category 2  
Eye irritation                : Category 2B  
Respiratory sensitization    : Category 1  
Skin sensitization            : Category 1B  
Germ cell mutagenicity      : Category 1B  
Carcinogenicity              : Category 1B  
Specific target organ toxicity : Category 3 (Respiratory system, Central nervous system)  
- single exposure  
Specific target organ toxicity : Category 1 (Central nervous system)  
- repeated exposure  
Short-term (acute) aquatic    : Category 3  
hazard  
Long-term (chronic) aquatic   : Category 3  
hazard

**GHS label elements**

## WABO PRIMALUB ADHESIVE

Version 1.0      Revision Date: 04/19/2022      SDS Number: 000000260428      Date of last issue: -  
Date of first issue: 04/19/2022

---

- Hazard pictograms : 
- Signal Word : Danger
- Hazard Statements : H226 Flammable liquid and vapor.  
H315 + H320 Causes skin and eye irritation.  
H332 Harmful if inhaled.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
H317 May cause an allergic skin reaction.  
H304 May be fatal if swallowed and enters airways.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H350 May cause cancer.  
H340 May cause genetic defects.  
H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure.  
H402 Harmful to aquatic life.  
H412 Harmful to aquatic life with long lasting effects.
- Precautionary Statements : **Prevention:**  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
P271 Use only outdoors or in a well-ventilated area.  
P201 Obtain special instructions before use.  
P260 Do not breathe dusts or mists.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P261 Avoid breathing mist.  
P202 Do not handle until all safety precautions have been read and understood.  
P273 Avoid release to the environment.  
P243 Take action to prevent static discharges.  
P284 In case of inadequate ventilation wear respiratory protection.  
P241 Use explosion-proof electrical/ ventilating/ lighting/ .? / equipment.  
P264 Wash face, hands and any exposed skin thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P242 Use only non-sparking tools.  
P240 Ground and bond container and receiving equipment.
- Response:**  
P308 + P311 IF exposed or concerned: Call a POISON CENTER/ doctor.
- Storage:**  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P233 Keep container tightly closed.

## WABO PRIMALUB ADHESIVE

Version 1.0      Revision Date: 04/19/2022      SDS Number: 000000260428      Date of last issue: -  
 Date of first issue: 04/19/2022

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/container to appropriate hazardous waste collection point.

**Other hazards**

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Isocyanates  
solvent(s)

**Components**

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), light arom.	64742-95-6	>= 10 -< 15
Distillates (petroleum), hydrotreated light	64742-47-8	>= 7 -< 15
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	>= 7 -< 10
Stoddard solvent	8052-41-3	>= 3 -< 10
Methylenediphenyl diisocyanate	26447-40-5	>= 3 -< 5
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9	>= 3 -< 5
Silicon dioxide	7631-86-9	>= 1 -< 5
disodium oxide	1313-59-3	>= 0.2 -< 1
Titanium dioxide	13463-67-7	>= 0.3 -< 1
Nonane	111-84-2	>= 0.1 -< 1
dipotassium oxide	12136-45-7	>= 0.1 -< 0.2
Polymethylene polyphenylisocyanate, polyethylene glycol polymer	57636-09-6	>= 0.1 -< 0.2

**SECTION 4. FIRST AID MEASURES**

General advice : First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled : Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

In case of skin contact : Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

		for at least 15 minutes. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. Immediate medical attention required.
If swallowed	:	Rinse mouth and then drink 200-300 ml of water. Do NOT induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.
Most important symptoms and effects, both acute and delayed	:	May be fatal if swallowed and enters airways. Causes skin and eye irritation. May cause an allergic skin reaction. Harmful if inhaled. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. May cause drowsiness or dizziness. May cause genetic defects. May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Notes to physician	:	Treat symptomatically.

---

**SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media	:	Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical
Unsuitable extinguishing media	:	High volume water jet
Hazardous combustion products	:	nitrous gases fumes/smoke isocyanate vapor
Specific extinguishing methods	:	Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.
Special protective equipment for fire-fighters	:	Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

---

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	:	Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment. Avoid contact with the skin, eyes and clothing. Avoid all sources of ignition: heat, sparks, open flame.
Environmental precautions	:	Prevent spread over a wide area (e.g. by containment or oil barriers). Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Move container to a well-ventilated area (outside).  
Spill area can be decontaminated with the following recommended decontamination solution:  
Mixture of 90 % water, 5-8 % household ammonia, 2-5 % detergent.  
Add at a 10 to 1 ratio.  
Allow solution to stand for at least 10 minutes.

---

## SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Sources of ignition should be kept well clear.  
Take precautionary measures against static discharges.  
Substance/product can form explosive mixture with air.  
Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.

Advice on safe handling : Provide suitable exhaust ventilation at the processing machines.  
Ensure thorough ventilation of stores and work areas.  
Avoid aerosol formation.  
Take precautionary measures against static discharges.  
Avoid contact with skin and eyes.  
When handling heated product, vapours of the product should be ventilated, and respiratory protection used.  
Wear respiratory protection when spraying.  
Danger of bursting when sealed gastight.  
If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.  
Protect against moisture.

Hygiene measures : When using, do not eat, drink or smoke.  
Hands and/or face should be washed before breaks and at the end of the shift.  
At the end of the shift the skin should be cleaned and skin-care agents applied.  
Gloves must be inspected regularly and prior to each use.  
Replace if necessary (e.g. pinhole leaks).  
Wash soiled clothing immediately.  
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.

Conditions for safe storage : Keep away from sources of ignition - No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

Further information on storage : Keep container tightly closed and in a well-ventilated place.

---

## WABO PRIMALUB ADHESIVE

Version 1.0      Revision Date: 04/19/2022      SDS Number: 000000260428      Date of last issue: -  
 Date of first issue: 04/19/2022

age conditions      Keep away from heat.  
 Avoid all sources of ignition: heat, sparks, open flame.

Recommended storage temperature : 10 - 32 °C  
 Further information on storage stability : Protect from direct sunlight.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated light	64742-47-8	TWA value	200 mg/m <sup>3</sup>	OEL (MX)
		TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH
Solvent naphtha (petroleum), light arom.	64742-95-6	TWA	200 mg/m <sup>3</sup> (total hydrocarbon vapor)	ACGIH
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	VLE-PPT	0.005 ppm	NOM-010-STPS-2014
		TWA	0.005 ppm	ACGIH
Stoddard solvent	8052-41-3	VLE-PPT	100 ppm	NOM-010-STPS-2014
		TWA	100 ppm	ACGIH

**Engineering measures** : Ensure adequate ventilation.

**Personal protective equipment**

**Respiratory protection** : When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place.  
 For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

**Hand protection**

**Remarks** : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

**Eye protection** : Safety glasses with side-shields.

**Skin and body protection** : Body protection must be chosen based on level of activity and exposure.  
 Antistatic apron

**Protective measures** : Do not inhale gases/vapours/aerosols.  
 Avoid contact with the skin, eyes and clothing.  
 Avoid exposure - obtain special instructions before use.  
 Handle in accordance with good building materials hygiene

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

and safety practice.  
Wearing of closed work clothing is recommended.  
Wear protective clothing as necessary to prevent contact.  
Eye wash fountains and safety showers must be easily accessible.  
Observe the appropriate PEL or TLV value.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Color	:	light gray
Odor	:	aromatic
Odor Threshold	:	not determined
pH	:	Not applicable
Melting point	:	No data available
Boiling point	:	> 100 °C
Flash point	:	42 °C
Evaporation rate	:	No data available
Flammability (liquids)	:	Flammable liquid and vapor.
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	No data available
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	1.02 g/cm <sup>3</sup> (20 °C)
Solubility(ies)		
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	Not applicable
Autoignition temperature	:	No data available
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Oxidizing properties : Not an oxidizer.

Sublimation point : No data available

Molecular weight : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No hazardous reactions if stored and handled as prescribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions : Vapors may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : No hazardous decomposition products if stored and handled as prescribed/indicated.

---

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity**

Harmful if inhaled.

**Product:**

Acute inhalation toxicity : ATE: 3.77 mg/l  
Remarks: Determined for mist

**Skin corrosion/irritation**

Causes skin irritation.

**Serious eye damage/eye irritation**

Causes eye irritation.

**Respiratory or skin sensitization****Skin sensitization**

May cause an allergic skin reaction.

**Respiratory sensitization**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Germ cell mutagenicity**

May cause genetic defects.





## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Additional ecological information : Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(STODDARD SOLVENT, SOLVENT NAPHTHA)

Class : 3

Packing group : III

Labels : 3

**IATA-DGR**

UN/ID No. : UN 1993

Proper shipping name : Flammable liquid, n.o.s.  
(STODDARD SOLVENT, SOLVENT NAPHTHA)

Class : 3

Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo aircraft) : 366

Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1993

Proper shipping name : FLAMMABLE LIQUID, N.O.S.  
(STODDARD SOLVENT, SOLVENT NAPHTHA)

Class : 3

Packing group : III

Labels : 3

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

EmS Code : F-E, S-E  
 Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Domestic regulation****Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**SECTION 15. REGULATORY INFORMATION****Safety, health and environmental regulations/legislation specific for the substance or mixture**

NOM-165-SEMARNAT-2013, Norm establishing a list of substances subject to report for the Registry of Emissions and Pollutant Transfer

Components	CAS-No.	MPU (kg/year)	Transfer/Release (kg/year)
Diphenylmethane-4,4'-diisocyanate (MDI)	101-68-8	5000 kg/year	100 kg/year
Isocyanic acid, polymethylenepolyphenylene ester (P-MDI)	9016-87-9	5000 kg/year	100 kg/year

MPU: Applicable reporting threshold when the substance, pure or in mixture in a composition of more than 1% by weight, is used for industrial activities at facilities that are subject to report or are produced by them

**SECTION 16. OTHER INFORMATION****Full text of other abbreviations**

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
 NOM-010-STPS-2014 : Mexico. Norm NOM-010-STPS-2014 on Chemicals Polluting the Work Environment - Identification, Assessment and Control - Appendix 1 Occupational Exposure Limits  
 OEL (MX) : Occupational Exposure Limit Values (Mexico)  
 ACGIH / TWA : 8-hour, time-weighted average  
 NOM-010-STPS-2014 / VLE- : Time weighted average limit value  
 PPT  
 OEL (MX) / TWA value : Time Weighted Average (TWA):

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and

## WABO PRIMALUB ADHESIVE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	04/19/2022	000000260428	Date of first issue: 04/19/2022

---

Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECL - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Revision Date : 04/19/2022

The information is considered as correct, but not exhaustive, and will be used only as a guide, which is based in the current knowledge of the substance or mixture, and is applicable to proper safety precautions for the product.

MX / EN