WABO NEOLUBE

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/25/2021 000000260043 Date of first issue: 05/25/2021

SECTION 1. IDENTIFICATION

Product name : WABO NEOLUBE Other means of identification : Part #2810, #2815

Manufacturer or supplier's details

Company name of supplier : Watson Bowman Acme Corp.

Address : 95 Pineview Drive Amherst, NY 14228

Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives and/or sealants

Restrictions on use : Reserved for industrial and professional use.

National Emergency : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

Telephone Number

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2B

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

Category 3 (Respiratory system)

Specific target organ toxicity

- repeated exposure

Category 2 (Central nervous system, Liver, Kidney, hearing or-

gans)

Aspiration hazard : Category 1

Short-term (acute) aquatic

hazard

Category 2

Long-term (chronic) aquatic

hazard

Category 3

GHS label elements

Hazard pictograms





Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

WABO NEOLUBE

 Version
 Revision Date:
 SDS Number:
 Date of last issue:

 1.0
 05/25/2021
 000000260043
 Date of first issue: 05/25/2021

H304 May be fatal if swallowed and enters airways.

H315 + H320 Causes skin and eye irritation.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs (Central nervous system, Liver, Kidney, hearing organs) through prolonged or repeated exposure.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

WABO NEOLUBE

Version Revision Date: SDS Number: Date of last issue: -

05/25/2021 000000260043 Date of first issue: 05/25/2021 1.0

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste dis-

posal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : organic

Components

Chemical name	CAS-No.	Concentration (% w/w)
xylene	1330-20-7	>= 25 - < 50
ethylbenzene	100-41-4	>= 5 - < 20
toluene	108-88-3	>= 5 - < 20

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice First aid personnel should pay attention to their own safety.

Immediately remove contaminated clothing.

If inhaled If difficulties occur after vapour/aerosol has been inhaled, re-

move to fresh air and seek medical attention.

In case of skin contact After contact with skin, wash immediately with plenty of water

and soap.

Under no circumstances should organic solvent be used.

If irritation develops, seek medical attention.

Hold eyes open and rinse slowly and gently with water for 15 In case of eye contact

to 20 minutes. Remove contact lenses, if present, after first 5

minutes, then continue rinsing.

If eye irritation persists, consult a specialist.

If swallowed Immediately rinse mouth and then drink 200-300 ml of water,

seek medical attention.

Do NOT induce vomiting.

Most important symptoms

and effects, both acute and

delayed

May be fatal if swallowed and enters airways.

Causes skin and eye irritation. May cause respiratory irritation.

Suspected of damaging the unborn child.

May cause damage to organs through prolonged or repeated

exposure.

Notes to physician Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Dry powder

Carbon dioxide (CO2)

Unsuitable extinguishing me- :

dia

WABO NEOLUBE

Version Revision Date: SDS Number: Date of last issue: -

05/25/2021 000000260043 Date of first issue: 05/25/2021 1.0

Specific hazards during fire

fighting

Hazardous combustion prod-

ucts

harmful vapours nitrogen oxides fumes/smoke carbon black carbon oxides

Further information The degree of risk is governed by the burning substance and

the fire conditions.

Containers may rocket or explode in heat of fire.

See SDS section 10 - Stability and reactivity.

If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not

allow to reach sewage or effluent systems.

Contaminated extinguishing water must be disposed of in ac-

cordance with official regulations.

Special protective equipment:

for fire-fighters

Wear a self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- :

tive equipment and emer-

gency procedures

Can release flammable vapours. Wind direction should be noted.

Avoid all sources of ignition: heat, sparks, open flame.

Use antistatic tools.

Breathing protection required. Use personal protective clothing.

Environmental precautions Contain contaminated water/firefighting water.

Do not discharge into drains/surface waters/groundwater.

Methods and materials for containment and cleaning up Large spills should be collected mechanically (remove by

pumping) for disposal.

Pick up with inert absorbent material (e.g. sand, earth etc.). Spilled product should be disposed in accordance with all ap-

plicable government regulations.

SECTION 7. HANDLING AND STORAGE

Advice on protection against

fire and explosion

Sources of ignition should be kept well clear.

Take precautionary measures against static discharges. Substance/product can form explosive mixture with air. Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ig-

nition.

Keep away from sources of ignition - No smoking. Advice on safe handling

Take precautionary measures against static discharges.

Avoid inhalation of mists/vapours.

Avoid skin contact.

Further information on stor-

age conditions

Keep container tightly closed in a cool, well-ventilated place.

Protect from direct sunlight.

Materials to avoid Oxidizing agents

WABO NEOLUBE

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/25/2021 000000260043 Date of first issue: 05/25/2021

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis
		(Form of ex-	ters / Permissible	
		posure)	concentration	
xylene	1330-20-7	PEL	100 ppm	29 CFR
			435 mg/m3	1910.1000
		TWA value	100 nnm	(Table Z-1) 29 CFR
		I WA Value	100 ppm 435 mg/m3	1910.1000
			433 mg/m3	(Table Z-1-A)
		STEL value	150 ppm	29 CFR
		0.22 (4.40	655 mg/m3	1910.1000
			J 22g	(Table Z-1-A)
		TWA	100 ppm	OSHA Z-1
			435 mg/m3	
		TWA	100 ppm	ACGIH
		STEL	150 ppm	ACGIH
		STEL	150 ppm	OSHA P0
			655 mg/m3	
		TWA	100 ppm	OSHA P0
	100 11 1	T14/4	435 mg/m3	A O O U ITI \ /
ethylbenzene	100-41-4	TWA value	20 ppm	ACGIHTLV
		STEL value	125 ppm	NIOSH
		REL value	545 mg/m3 100 ppm	NIOSH
		REL Value	435 mg/m3	NIOSH
		PEL	100 ppm	29 CFR
		'	435 mg/m3	1910.1000
			,	(Table Z-1)
		TWA value	100 ppm	29 CFR
			435 mg/m3	1910.1000
				(Table Z-1-A)
		STEL value	125 ppm	29 CFR
			545 mg/m3	1910.1000
		T14/4	00	(Table Z-1-A)
		TWA	20 ppm	ACGIH
		TWA	100 ppm 435 mg/m3	NIOSH REL
		ST	125 ppm	NIOSH REL
			545 mg/m3	NICOTTICE
		TWA	100 ppm	OSHA Z-1
			435 mg/m3	
		TWA	100 ppm	OSHA P0
			435 mg/m3	
		STEL	125 ppm	OSHA P0
			545 mg/m3	
toluene	108-88-3	TWA value	20 ppm	ACGIHTLV
		REL value	100 ppm	NIOSH
			375 mg/m3	

WABO NEOLUBE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/25/2021	000000260043	Date of first issue: 05/25/2021

STEL value	150 ppm 560 mg/m3	NIOSH
TWA value	100 ppm 375 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
STEL value	150 ppm 560 mg/m3	29 CFR 1910.1000 (Table Z-1-A)
max. conc.	500 ppm	29 CFR 1910.1000 (Table Z-2)
CLV	300 ppm	29 CFR 1910.1000 (Table Z-2)
TWA value	200 ppm	29 CFR 1910.1000 (Table Z-2)
TWA	20 ppm	ACGIH
TWA	100 ppm 375 mg/m3	NIOSH REL
ST	150 ppm 560 mg/m3	NIOSH REL
TWA	200 ppm	OSHA Z-2
CEIL	300 ppm	OSHA Z-2
Peak	500 ppm (10 minutes)	OSHA Z-2
TWA	100 ppm 375 mg/m3	OSHA P0
STEL	150 ppm 560 mg/m3	OSHA P0

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupa-

tional exposure limits they must use appropriate certified res-

pirators.

Wear a NIOSH-certified (or equivalent) organic vapour/partic-

ulate respirator as needed.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's di-

rections for use should be observed because of great diver-

sity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity

and exposure.

Protective measures : Do not inhale gases/vapours/aerosols.

Avoid contact with the skin, eyes and clothing.

Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene

and safety practice.

Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

WABO NEOLUBE

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/25/2021 000000260043 Date of first issue: 05/25/2021

Hands and/or face should be washed before breaks and at

the end of the shift.

At the end of the shift the skin should be cleaned and skin-

care agents applied.

Remove contaminated clothing immediately and clean before

re-use or dispose it if necessary.

Gloves must be inspected regularly and prior to each use.

Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : amber

Odor : aromatic

Odor Threshold : not determined

pH : Not applicable

Melting point : not determined

Boiling point : 230 °F / 110 °C

Flash point : 39 °F / 4 °C

Evaporation rate : not determined

Flammability (liquids) : Highly flammable liquid and vapor.

Self-ignition : not self-igniting

Upper explosion limit / Upper

flammability limit

7 %(V)

Lower explosion limit / Lower :

flammability limit

1.1 %(V)

Vapor pressure : 29 hPa (68 °F / 20 °C)

Relative vapor density : No data available

Relative density : No data available

Density : 0.94 g/cm3 (68 °F / 20 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-oc-

tanol/water

No data available

WABO NEOLUBE

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/25/2021 000000260043 Date of first issue: 05/25/2021

Autoignition temperature : 932 °F / 500 °C

Decomposition temperature : No decomposition if stored and handled as prescribed/indi-

cated.

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Explosive properties : Not explosive

Sublimation point : No data available

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No hazardous reactions if stored and handled as pre-

scribed/indicated.

Chemical stability : The product is stable if stored and handled as prescribed/indi-

cated.

Possibility of hazardous reac-

tions

The product is stable if stored and handled as prescribed/indi-

cated.

Conditions to avoid : Avoid all sources of ignition: heat, sparks, open flame.

Avoid extreme heat.

Avoid heating under confinement.

Incompatible materials Hazardous decomposition

products

Oxidizing agents
Carbon dioxide (CO2)
Carbon monoxide

Gaseous hydrogen chloride (HCI).

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes eye irritation.

Respiratory or skin sensitization

Skin sensitization

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

WABO NEOLUBE

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/25/2021 000000260043 Date of first issue: 05/25/2021

Carcinogenicity

Not classified based on available information.

IARC Group 2B: Possibly carcinogenic to humans

ethylbenzene 100-41-4

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Central nervous system, Liver, Kidney, hearing organs) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : The product has not been tested. The statements on toxicol-

ogy have been derived from the properties of the individual

components.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological infor-

mation

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual

components.

WABO NEOLUBE

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/25/2021 000000260043 Date of first issue: 05/25/2021

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with national, state and local regula-

tions.

Do not contaminate ponds, waterways or ditches with chemi-

cal or used container.

Do not discharge into drains/surface waters/groundwater.

Contaminated packaging : Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thor-

oughly cleaned.

Contaminated packaging should be emptied as far as possible

and disposed of in the same manner as the substance/prod-

uct.

364

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

UN/ID No. : UN 1133
Proper shipping name : ADHESIVES

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo :

aircraft)

Packing instruction (passen: 353

ger aircraft)

IMDG-Code

UN number : UN 1133 Proper shipping name : ADHESIVES

Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

UN/ID/NA number : UN 1133
Proper shipping name : ADHESIVES

Class : 3 Packing group : II

Labels : FLAMMABLE LIQUID

ERG Code : 128 Marine pollutant : no

WABO NEOLUBE

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/25/2021 000000260043 Date of first issue: 05/25/2021

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
xylene	1330-20-7	100	200
	: The following components are subject to reporting levels established by SARA Title III, Section 313:		

xylene 1330-20-7 >= 30 - < 50 %

ethylbenzene 100-41-4 >= 10 - < 20 % toluene 108-88-3 >= 10 - < 20 %

US State Regulations

Pennsylvania Right To Know

 xylene
 1330-20-7

 ethylbenzene
 100-41-4

 toluene
 108-88-3

 formaldehyde
 50-00-0

New Jersey Right To Know

 xylene
 1330-20-7

 ethylbenzene
 100-41-4

 toluene
 108-88-3

California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer, and

toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION


Further information

WABO NEOLUBE

Version **Revision Date:** SDS Number: Date of last issue: -

05/25/2021 000000260043 Date of first issue: 05/25/2021 1.0

NFPA 704:



Special hazard

HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z- : OSHA - Table Z-1-A (29 CFR 1910.1000)

1)

29 CFR 1910.1000 (Table Z-OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR

1910.1000

29 CFR 1910.1000 (Table Z- : OSHA Table Z-2 (Toxic and Hazardous Substances) 29 CFR

1910.1000

2) **ACGIH** USA. ACGIH Threshold Limit Values (TLV)

American Conference of Governmental Industrial Hygienists -**ACGIHTLV**

threshold limit values (US)

NIOSH Pocket Guide to Chemical Hazards (US) NIOSH **NIOSH REL** USA. NIOSH Recommended Exposure Limits

OSHA P0 USA. OSHA - TABLE Z-1 Limits for Air Contaminants -

1910.1000

OSHA Z-1 USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

OSHA Z-2 USA. Occupational Exposure Limits (OSHA) - Table Z-2

29 CFR 1910.1000 (Table Z-

1-A) / STEL value

Short Term Exposure Limit (STEL):

Time Weighted Average (TWA):

29 CFR 1910.1000 (Table Z-Time Weighted Average (TWA):

1-A) / TWA value

29 CFR 1910.1000 (Table Z- : Permissible exposure limit

1) / PEL

29 CFR 1910.1000 (Table Z- :

Ceiling Limit Value: 2) / CLV

29 CFR 1910.1000 (Table Z- :

2) / TWA value

29 CFR 1910.1000 (Table Z-Maximum concentration:

2) / max. conc.

ACGIH / TWA 8-hour, time-weighted average Short-term exposure limit ACGIH / STEL Time Weighted Average (TWA): ACGIHTLV / TWA value NIOSH / REL value Recommended exposure limit (REL): NIOSH / STEL value Short Term Exposure Limit (STEL):

WABO NEOLUBE

Version 1.0	Revision Date: 05/25/2021		Number: 000260043	Date of last issue: - Date of first issue: 05/25/2021	
NIOS	H REL / TWA	: -	Time-weighted	average concentration for up to a 10-hour	
				g a 40-hour workweek	
NIOS	H REL / ST	: \$	STEL - 15-min	ute TWA exposure that should not be exceeded ing a workday	
OSH/	HA P0 / TWA : 8-hour time weighted average				
	A PO / STEL		: Short-term exposure limit		
OSH/	4 Z-1 / TWA		: 8-hour time weighted average		
OSH/	A Z-2 / TWA		: 8-hour time weighted average		
OSH/	4 Z-2 / CEIL		: Acceptable ceiling concentration		
			ximum peak above the acceptable ceiling con-		

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS -Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/25/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

WABO NEOLUBE

Version Revision Date: SDS Number: Date of last issue: -

1.0 05/25/2021 000000260043 Date of first issue: 05/25/2021

US / EN