

WABO NEOLUBE

Version 1.0 Revision Date: 05/25/2021 SDS Number: 000000260043 Date of last issue: -
Date of first issue: 05/25/2021

SECTION 1. IDENTIFICATION

Product name : WABO NEOLUBE
Other means of identification : Part #2810, #2815

Manufacturer or supplier's details

Company name of supplier : Watson Bowman Acme Corp.
Address : 95 Pineview Drive
Amherst, NY 14228
Emergency telephone : ChemTel: +1-813-248-0585

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives and/or sealants
Restrictions on use : Reserved for industrial and professional use.

National Emergency Telephone Number : USA: +1-800-255-3924 ChemTel contract no. MIS9240420

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 2
Skin irritation : Category 2
Eye irritation : Category 2B
Reproductive toxicity : Category 2
Specific target organ toxicity - single exposure : Category 3 (Respiratory system)
Specific target organ toxicity - repeated exposure : Category 2 (Central nervous system, Liver, Kidney, hearing organs)
Aspiration hazard : Category 1
Short-term (acute) aquatic hazard : Category 2
Long-term (chronic) aquatic hazard : Category 3

GHS label elements

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H225 Highly flammable liquid and vapor.

WABO NEOLUBE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/25/2021	00000260043	Date of first issue: 05/25/2021

H304 May be fatal if swallowed and enters airways.
H315 + H320 Causes skin and eye irritation.
H335 May cause respiratory irritation.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs (Central nervous system, Liver, Kidney, hearing organs) through prolonged or repeated exposure.
H401 Toxic to aquatic life.
H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements

:

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P332 + P313 If skin irritation occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.

WABO NEOLUBE

Version 1.0 Revision Date: 05/25/2021 SDS Number: 00000260043 Date of last issue: -
 Date of first issue: 05/25/2021

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : organic

Components

Chemical name	CAS-No.	Concentration (% w/w)
xylene	1330-20-7	>= 25 - < 50
ethylbenzene	100-41-4	>= 5 - < 20
toluene	108-88-3	>= 5 - < 20

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled : If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

In case of skin contact : After contact with skin, wash immediately with plenty of water and soap.
Under no circumstances should organic solvent be used.
If irritation develops, seek medical attention.

In case of eye contact : Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.
If eye irritation persists, consult a specialist.

If swallowed : Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.
Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed : May be fatal if swallowed and enters airways.
Causes skin and eye irritation.
May cause respiratory irritation.
Suspected of damaging the unborn child.
May cause damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : water jet

WABO NEOLUBE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/25/2021	00000260043	Date of first issue: 05/25/2021

- Specific hazards during fire fighting : See SDS section 10 - Stability and reactivity.
- Hazardous combustion products : harmful vapours
nitrogen oxides
fumes/smoke
carbon black
carbon oxides
- Further information : The degree of risk is governed by the burning substance and the fire conditions.
Containers may rocket or explode in heat of fire.
If exposed to fire, keep containers cool by spraying with water.
Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.
Contaminated extinguishing water must be disposed of in accordance with official regulations.
- Special protective equipment for fire-fighters : Wear a self-contained breathing apparatus.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Can release flammable vapours.
Wind direction should be noted.
Avoid all sources of ignition: heat, sparks, open flame.
Use antistatic tools.
Breathing protection required.
Use personal protective clothing.
- Environmental precautions : Contain contaminated water/firefighting water.
Do not discharge into drains/surface waters/groundwater.
- Methods and materials for containment and cleaning up : Large spills should be collected mechanically (remove by pumping) for disposal.
Pick up with inert absorbent material (e.g. sand, earth etc.).
Spilled product should be disposed in accordance with all applicable government regulations.
-

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Sources of ignition should be kept well clear.
Take precautionary measures against static discharges.
Substance/product can form explosive mixture with air.
Vapours are heavier than air and may accumulate in low areas and travel a considerable distance up to the source of ignition.
- Advice on safe handling : Keep away from sources of ignition - No smoking.
Take precautionary measures against static discharges.
Avoid inhalation of mists/vapours.
Avoid skin contact.
- Further information on storage conditions : Keep container tightly closed in a cool, well-ventilated place.
Protect from direct sunlight.
- Materials to avoid : Oxidizing agents
-

WABO NEOLUBE

Version 1.0 Revision Date: 05/25/2021 SDS Number: 00000260043 Date of last issue: -
 Date of first issue: 05/25/2021

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis		
xylene	1330-20-7	PEL	100 ppm 435 mg/m ³	29 CFR 1910.1000 (Table Z-1)		
		TWA value	100 ppm 435 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)		
		STEL value	150 ppm 655 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)		
		TWA	100 ppm 435 mg/m ³	OSHA Z-1		
		TWA	100 ppm	ACGIH		
		STEL	150 ppm	ACGIH		
		STEL	150 ppm 655 mg/m ³	OSHA P0		
		TWA	100 ppm 435 mg/m ³	OSHA P0		
		ethylbenzene	100-41-4	TWA value	20 ppm	ACGIHTLV
				STEL value	125 ppm 545 mg/m ³	NIOSH
REL value	100 ppm 435 mg/m ³			NIOSH		
PEL	100 ppm 435 mg/m ³			29 CFR 1910.1000 (Table Z-1)		
TWA value	100 ppm 435 mg/m ³			29 CFR 1910.1000 (Table Z-1-A)		
STEL value	125 ppm 545 mg/m ³			29 CFR 1910.1000 (Table Z-1-A)		
TWA	20 ppm			ACGIH		
TWA	100 ppm 435 mg/m ³			NIOSH REL		
ST	125 ppm 545 mg/m ³			NIOSH REL		
TWA	100 ppm 435 mg/m ³			OSHA Z-1		
toluene	108-88-3	TWA	100 ppm 435 mg/m ³	OSHA P0		
		STEL	125 ppm 545 mg/m ³	OSHA P0		
		TWA value	20 ppm	ACGIHTLV		
		REL value	100 ppm 375 mg/m ³	NIOSH		

WABO NEOLUBE

Version 1.0 Revision Date: 05/25/2021 SDS Number: 000000260043 Date of last issue: -
 Date of first issue: 05/25/2021

		STEL value	150 ppm 560 mg/m ³	NIOSH
		TWA value	100 ppm 375 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		STEL value	150 ppm 560 mg/m ³	29 CFR 1910.1000 (Table Z-1-A)
		max. conc.	500 ppm	29 CFR 1910.1000 (Table Z-2)
		CLV	300 ppm	29 CFR 1910.1000 (Table Z-2)
		TWA value	200 ppm	29 CFR 1910.1000 (Table Z-2)
		TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m ³	NIOSH REL
		ST	150 ppm 560 mg/m ³	NIOSH REL
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm (10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m ³	OSHA P0
		STEL	150 ppm 560 mg/m ³	OSHA P0

Engineering measures : Ensure adequate ventilation.

Personal protective equipment

Respiratory protection : When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.
 Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator as needed.

Hand protection

Remarks : Wear chemical resistant protective gloves. Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Body protection must be chosen based on level of activity and exposure.

Protective measures : Do not inhale gases/vapours/aerosols.
 Avoid contact with the skin, eyes and clothing.
 Avoid exposure - obtain special instructions before use.
 Handle in accordance with good building materials hygiene and safety practice.
 Wearing of closed work clothing is recommended.

Hygiene measures : When using, do not eat, drink or smoke.

WABO NEOLUBE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/25/2021	000000260043	Date of first issue: 05/25/2021

Hands and/or face should be washed before breaks and at the end of the shift.
At the end of the shift the skin should be cleaned and skin-care agents applied.
Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.
Gloves must be inspected regularly and prior to each use.
Replace if necessary (e.g. pinhole leaks).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	amber
Odor	:	aromatic
Odor Threshold	:	not determined
pH	:	Not applicable
Melting point	:	not determined
Boiling point	:	230 °F / 110 °C
Flash point	:	39 °F / 4 °C
Evaporation rate	:	not determined
Flammability (liquids)	:	Highly flammable liquid and vapor.
Self-ignition	:	not self-igniting
Upper explosion limit / Upper flammability limit	:	7 %(V)
Lower explosion limit / Lower flammability limit	:	1.1 %(V)
Vapor pressure	:	29 hPa (68 °F / 20 °C)
Relative vapor density	:	No data available
Relative density	:	No data available
Density	:	0.94 g/cm ³ (68 °F / 20 °C)
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-oc-tanol/water	:	No data available

WABO NEOLUBE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/25/2021	000000260043	Date of first issue: 05/25/2021

Autoignition temperature	:	932 °F / 500 °C
Decomposition temperature	:	No decomposition if stored and handled as prescribed/indicated.
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Explosive properties	:	Not explosive
Sublimation point	:	No data available
Molecular weight	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No hazardous reactions if stored and handled as prescribed/indicated.
Chemical stability	:	The product is stable if stored and handled as prescribed/indicated.
Possibility of hazardous reactions	:	The product is stable if stored and handled as prescribed/indicated.
Conditions to avoid	:	Avoid all sources of ignition: heat, sparks, open flame. Avoid extreme heat. Avoid heating under confinement.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	Carbon dioxide (CO ₂) Carbon monoxide Gaseous hydrogen chloride (HCl).

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes eye irritation.

Respiratory or skin sensitization**Skin sensitization**

Not classified based on available information.

Respiratory sensitization

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

WABO NEOLUBE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/25/2021	000000260043	Date of first issue: 05/25/2021

Carcinogenicity

Not classified based on available information.

IARC	Group 2B: Possibly carcinogenic to humans ethylbenzene	100-41-4
-------------	---	----------

Reproductive toxicity

Suspected of damaging the unborn child.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

May cause damage to organs (Central nervous system, Liver, Kidney, hearing organs) through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Further information**Product:**

Remarks	:	The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.
---------	---	---

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Product:****Ecotoxicology Assessment**

Acute aquatic toxicity	:	Toxic to aquatic life.
------------------------	---	------------------------

Chronic aquatic toxicity	:	Harmful to aquatic life with long lasting effects.
--------------------------	---	--

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects**Product:**

Additional ecological information	:	Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.
-----------------------------------	---	---

WABO NEOLUBE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/25/2021	000000260043	Date of first issue: 05/25/2021

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Dispose of in accordance with national, state and local regulations.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Do not discharge into drains/surface waters/groundwater.
- Contaminated packaging : Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.
Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.
-

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

- UN/ID No. : UN 1133
Proper shipping name : ADHESIVES
Class : 3
Packing group : II
Labels : Flammable Liquids
Packing instruction (cargo aircraft) : 364
Packing instruction (passenger aircraft) : 353

IMDG-Code

- UN number : UN 1133
Proper shipping name : ADHESIVES
Class : 3
Packing group : II
Labels : 3
EmS Code : F-E, S-D
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation**49 CFR**

- UN/ID/NA number : UN 1133
Proper shipping name : ADHESIVES
Class : 3
Packing group : II
Labels : FLAMMABLE LIQUID
ERG Code : 128
Marine pollutant : no

WABO NEOLUBE

Version 1.0 Revision Date: 05/25/2021 SDS Number: 000000260043 Date of last issue: -
 Date of first issue: 05/25/2021

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylene	1330-20-7	100	200

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

xylene	1330-20-7	>= 30 - < 50 %
ethylbenzene	100-41-4	>= 10 - < 20 %
toluene	108-88-3	>= 10 - < 20 %

US State Regulations**Pennsylvania Right To Know**

xylene	1330-20-7
ethylbenzene	100-41-4
toluene	108-88-3
formaldehyde	50-00-0

New Jersey Right To Know

xylene	1330-20-7
ethylbenzene	100-41-4
toluene	108-88-3

California Prop. 65

WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The ingredients of this product are reported in the following inventories:


TSCA	: All substances listed as active on the TSCA inventory
DSL	: All components of this product are on the Canadian DSL

SECTION 16. OTHER INFORMATION**Further information**

WABO NEOLUBE

Version
1.0Revision Date:
05/25/2021SDS Number:
000000260043Date of last issue: -
Date of first issue: 05/25/2021

NFPA 704:



HMIS® IV:

HEALTH		
FLAMMABILITY		
PHYSICAL HAZARD		

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

29 CFR 1910.1000 (Table Z-1-A)	: OSHA - Table Z-1-A (29 CFR 1910.1000)
29 CFR 1910.1000 (Table Z-1)	: OSHA - Table Z-1 (Limits for Air Contaminants) 29 CFR 1910.1000
29 CFR 1910.1000 (Table Z-2)	: OSHA Table Z-2 (Toxic and Hazardous Substances) 29 CFR 1910.1000
ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIHTLV	: American Conference of Governmental Industrial Hygienists - threshold limit values (US)
NIOSH	: NIOSH Pocket Guide to Chemical Hazards (US)
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA P0	: USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-2	: USA. Occupational Exposure Limits (OSHA) - Table Z-2
29 CFR 1910.1000 (Table Z-1-A) / STEL value	: Short Term Exposure Limit (STEL):
29 CFR 1910.1000 (Table Z-1-A) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-1) / PEL	: Permissible exposure limit
29 CFR 1910.1000 (Table Z-2) / CLV	: Ceiling Limit Value:
29 CFR 1910.1000 (Table Z-2) / TWA value	: Time Weighted Average (TWA):
29 CFR 1910.1000 (Table Z-2) / max. conc.	: Maximum concentration:
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
ACGIHTLV / TWA value	: Time Weighted Average (TWA):
NIOSH / REL value	: Recommended exposure limit (REL):
NIOSH / STEL value	: Short Term Exposure Limit (STEL):

WABO NEOLUBE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/25/2021	000000260043	Date of first issue: 05/25/2021

NIOSH REL / TWA	:	Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	:	STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA P0 / TWA	:	8-hour time weighted average
OSHA P0 / STEL	:	Short-term exposure limit
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-2 / TWA	:	8-hour time weighted average
OSHA Z-2 / CEIL	:	Acceptable ceiling concentration
OSHA Z-2 / Peak	:	Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 05/25/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

WABO NEOLUBE

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	05/25/2021	000000260043	Date of first issue: 05/25/2021

US / EN